STEEL PIPE NIPPLES





Standard Welded



MATERIAL SPECIFICATIONS

Dimensional: ASTM A733

Material: ASTM A53 Type F or Type E Galvanizing: Hot Dip Galvanizing* Threading:** NPT per ASME B 1.20.1

Anvil International is the only manufacturer where you can combine your import and U.S. Manufactured product requirements.

- Ends are cut square to the central axis. All burrs on the inside are removed. The ends of the pipe nipples are chamfered on the
 outside at an angle of 35° +/- 10° to the central axis.
- · Pipe nipples are threaded on both ends with standard NPT tapered threads. Threads are right hand on both ends.

ALSO AVAILABLE:

- Ready Cut Pipe, Standard Schd. 40 (black and galvanized) Pipe Size: 1/2", 3/4", 1", 11/4", 11/2", 2" Pipe Length: 8", 24", 30", 48", 60", 72"
- "66" Packs, Standard Schd. 40 (black and galvanized) Nipple Size: 1/2", 3/4", 1", 11/4", 11/2", 2"
- Single Run Nipple Packs (black and galvanized) Pipe Size: 1/2", 3/4", 1, 11/4", 11/2", 2"

STANDARD WELDED																		
Pipe Size	Pipe O.D.	Length Close	Pipe Nipple Lengths (Black and Galvanized)															
(in.)	(in.)	(in.)	The hippie teligins (block and outfullized)															
1/8	.405	3/4	11/2	2	21/2	3	31/2	4	41/2	5	51/2	6	7	8	9	10	11	12
1/4	.540	7/8	1½	2	21/2	3	31/2	4	41/2	5	51/2	6	7	8	9	10	11	12
¾	.675	1	11/2	2	21/2	3	31/2	4	41/2	5	51/2	6	7	8	9	10	11	12
1/2	.840	1%	11/2	2	21/2	3	31/2	4	41/2	5	51/2	6	7	8	9	10	11	12
3/4	1.050	1%	1½	2	21/2	3	31/2	4	41/2	5	51/2	6	7	8	9	10	11	12
1	1.315	1½		2	21/2	3	31/2	4	41/2	5	51/2	6	7	8	9	10	11	12
1¼	1.660	1%		2	21/2	3	31/2	4	41/2	5	51/2	6	7	8	9	10	11	12
1½	1.900	1¾	i i	2	21/2	3	31/2	4	41/2	5	51/2	6	7	8	9	10	11	12
2	2.375	2			21/2	3	31/2	4	41/2	5	51/2	6	7	8	9	10	11	12
21/2	2.875	21/2				3	31/2	4	41/2	5	51/2	6	7	8	9	10	11	12
3	3.500	2%				3	31/2	4	41/2	5	51/2	6	7	8	9	10	11	12
4	4.500	21/8						4	41/2	5	51/2	6	7	8	9	10	11	12
6	6.625	3%						4	41/2	5	51/2	6	7	8	9	10	11	12

^{*}Galvanized nipples are manufactured from pipe coated on the inside and outside by hot dip process.

^{**}British Standard threading per BS 21 available upon request.